



S-OIL SEVEN BLUE #5 CF

MONO GRADE OIL FOR DIESEL ENGINE

Product Description

S-OIL SEVEN BLUE #5 CF is developed to answer to the very severe technical constraints of the new low emission Diesel engines. For all turbocharged or normally aspirated diesel engines of vehicles operating in the most severe conditions whatever the seasons. And it can be used for vehicles requiring performance specification API CF.

Applications

- Suitable to all turbocharged or normally aspirated diesel engines of civil works machines, trucks, fishing boats, locomotives
- Responds to the API CF specifications for new low emission engines using low sulfur fuels

Features and Potential Benefits

- Very high viscosity index and good viscosity stability in operation
- Exceptional detergency level and soot dispersion properties
- High performance level insures safer and longer drains intervals

Performance Level

- API : CF

Typical Properties

Test Items	Method	Unit	40	50	70	
SG	ASTM D1298	-	0.8852	0.8911	0.8956	
Viscosity	40°C	ASTM D445	cSt	142.4	228.6	335.5
	100°C	ASTM D445	cSt	14.77	20.14	25.73
VI	ASTM D2270	-	103	102	100	
HTHS	ASTM D4683	-	4.3	5.5	6.7	
Flash Point	ASTM D92	°C	280	282	288	
Pour Point	ASTM D97	°C	-24	-15	-12	

S-OIL CORPORATION
192, Baekbeom-ro, Mapo-gu,
Seoul, 04196, Korea

S-OIL SEVEN BLUE #5 CF
2022.07.07

This lubricant used recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet is obtainable via your commercial adviser.