

MATERIAL SAFETY DATA SHEET

S-OIL PROCESS OIL 60

Date of the previous version: 2018-02-22

Revision Date: 2023-09-11

Version 3

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1. Product identifier**

Product name S-OIL PROCESS OIL 60
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Process oil.

1.3. Details of the supplier of the safety data sheet

Supplier S-OIL CORPORATION
192, Baekbeom-ro, Mapo-gu,
Seoul 04196, Korea

For further information, please contact:

Contact Point HSSEQ
E-mail Address dolyoo@stlc.co.kr

1.4. Emergency telephone number

Korea +82 2 3772 5655

2. HAZARDS IDENTIFICATION**2.1. Classification of the substance or mixture**

Classification
Aspiration hazard toxicity - Category 1

Symbol(s)

**2.2. Label elements**

Signal word Danger

2.3. hazards Statement

H304 May be fatal if swallowed and enters airways

2.4. Precautionary Statements

Prevention Not classified

Response
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P331 Do NOT induce vomiting.

Storage

MATERIAL SAFETY DATA SHEET

S-OIL PROCESS OIL 60

Date of the previous version: 2018-02-22

Revision Date: 2023-09-11

Version 3

P405 Store locked up.

Dispose
P501 Dispose of contents/container to follow the relevant regulations.

2.5. Other hazards

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

Environmental properties Should not be released into the environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS**3.1. Mixture**

| Chemical Name | CAS-No | EC-No | Weight % |
|--|------------|-----------|----------|
| Distillates (petroleum), hydrotreated light paraffinic | 64742-55-8 | 265-158-7 | 100 |

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

4. FIRST AID MEASURES**4.1. Description of first-aid measures**

General advice IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

Eye contact Rinse thoroughly with plenty of water, also under the eyelids.

Skin contact Remove contaminated clothing and shoes. Wash skin with soap and water. Wash contaminated clothing before reuse. High pressure jets may cause skin damage. In this case, the casualty should be sent immediately to hospital.

Inhalation Move to fresh air.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

4.2. Most important symptoms and effects, both acute and delayed

Eye contact Not classified.

Skin contact Not classified. High pressure injection of the products under the skin may have very serious consequences even though no symptom or injury may be apparent.

Inhalation Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.

Ingestion Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

MATERIAL SAFETY DATA SHEET**S-OIL PROCESS OIL 60**

Date of the previous version: 2018-02-22

Revision Date: 2023-09-11

Version 3

5.1. Extinguishing media

Suitable extinguishing media Carbon dioxide (CO₂). ABC powder. Foam. Water spray or fog.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.

5.3. Advice for fire-fighters

Special protective equipment for fire-fighters Wear self-contained breathing apparatus and protective suit.

Other information Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

6. ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

6.2. Environmental precautions

General Information Do not allow material to contaminate ground water system. Try to prevent the material from entering drains or water courses.
Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Methods for containment Dam up. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Personal Protective Equipment See Section 8 for more detail.

Waste treatment See section 13.

7. HANDLING AND STORAGE**7.1. Precautions for safe handling**

Advice on safe handling When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.

Prevention of fire and Take precautionary measures against static discharges. Ground/bond containers, tanks

Version GHS

MATERIAL SAFETY DATA SHEET

S-OIL PROCESS OIL 60

Date of the previous version: 2018-02-22

Revision Date: 2023-09-11

Version 3

| | |
|------------------|--|
| explosion | and transfer/receiving equipment. |
| Hygiene measures | Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets. |

7.2. Conditions for safe storage, including any incompatibilities

| | |
|---------------------------------------|---|
| Technical measures/Storage conditions | Keep away from food, drink and animal feeding stuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture. |
| Materials to Avoid | Strong oxidizing agents. |

7.3. Specific end uses

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

| | |
|-----------------|--|
| Exposure limits | Mineral oil mist : USA: OSHA (PEL) TWA 5 mg/m ³ , NIOSH (REL) TWA 5 mg/m ³ , STEL 10 mg/m ³ , ACGIH (TLV) TWA 5 mg/m ³ (highly refined) |
| Legend | See section 16. |

8.2. Exposure controls

Occupational Exposure Controls

| | |
|----------------------|--|
| Engineering Measures | Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment. |
|----------------------|--|

Personal Protective Equipment

| | |
|--------------------------|---|
| General Information | If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied. |
| Respiratory protection | None under normal use conditions. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses. |
| Eye Protection | If splashes are likely to occur, wear: Safety glasses with side-shields. |
| Skin and body protection | Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing. |
| Hand Protection | Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. If used in solution, or |

MATERIAL SAFETY DATA SHEET

S-OIL PROCESS OIL 60

Date of the previous version: 2018-02-22

Revision Date: 2023-09-11

Version 3

mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves.

Environmental exposure controls

General Information

The product should not be allowed to enter drains, water courses or the soil.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

| | | | |
|------------------------------------|------------------------|--------------------------|---|
| Color | | Bright and clear | |
| Physical State @20°C | | liquid | |
| Odor | | Characteristic | |
| <u>Property</u> | <u>Values</u> | <u>Remarks</u> | <u>Method</u> |
| pH | | Not applicable | |
| Boiling point/boiling range | | Not applicable | |
| Flash point | 158 °C 316 °F | | Cleveland Open Cup (COC) Cleveland Open Cup (COC)) |
| Evaporation rate | | No information available | |
| Flammability Limits in Air | | No information available | |
| Vapor Pressure | | No information available | |
| Vapor density | | No information available | |
| Density | 819kg/m ³ | @ 15 °C | |
| Water solubility | | Insoluble | |
| Solubility in other solvents | | No information available | |
| logPow | | No information available | |
| Autoignition temperature | | No information available | |
| Viscosity, kinematic | 7.60mm ² /s | @ 40 °C | |
| Explosive properties | Not explosive | | |
| Oxidizing Properties | Not applicable | | |
| Possibility of hazardous reactions | Not applicable | | |

9.2. Other information

10. STABILITY AND REACTIVITY

10.1. Reactivity

General Information

No information available.

10.2. Chemical stability

Stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous Reactions

None under normal processing.

10.4. Conditions to Avoid

Conditions to Avoid

Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.)

10.5. Incompatible Materials

Materials to Avoid

Strong oxidizing agents.

MATERIAL SAFETY DATA SHEET

S-OIL PROCESS OIL 60

Date of the previous version: 2018-02-22

Revision Date: 2023-09-11

Version 3

10.6. Hazardous Decomposition Products

Hazardous Decomposition Product None under normal use.

11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity Local effects Product Information

Skin contact . Not classified. High pressure injection of the products under the skin may have very serious consequences even though no symptom or injury may be apparent.

Eye contact . Not classified.

Inhalation . Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system

Ingestion . Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Acute toxicity- Component Information

| Chemical name | Oral | Dermal | Inhalation |
|--|-------------------------|----------------------------|--|
| Distillates (petroleum), hydrotreated light paraffinic | LD50 > 5000 mg/kg (rat) | LD50 > 5000 mg/kg (rabbit) | LC50 (4hr) > 5.53 mg/l (dust/mist) (rat) |

Sensitization

Sensitization Not classified as a sensitizer.

Specific effects

Carcinogenicity This product is not classified carcinogenic.
Mutagenicity This product is not classified as mutagenic.
Reproductive toxicity This product does not present any known or suspected reproductive hazards.

Repeated Dose Toxicity

Subchronic toxicity No information available.

Target Organ Effects (STOT)

Target Organ Effects (STOT) No information available.

Other information

Other adverse effects Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing).

| Chemical name | Aspiration Hazard |
|--|----------------------------------|
| Distillates (petroleum), hydrotreated light paraffinic | Aspiration toxicity – Category 1 |

12. ECOLOGICAL INFORMATION

12.1. Toxicity

MATERIAL SAFETY DATA SHEET

S-OIL PROCESS OIL 60

Date of the previous version: 2018-02-22

Revision Date: 2023-09-11

Version 3

Not classified.

Aquatic toxicity - Product Information

| Chemical name | Toxicity to algae | Toxicity to daphnia and other aquatic invertebrates | Toxicity to fish |
|--|--------------------------------|---|-------------------------------|
| Distillates (petroleum), hydrotreated light paraffinic | IC50 > 1000 mg/l (72hr, Algae) | EC50 > 1000 mg/l (48hr, Daphnia) | LC50 > 1000 mg/l (96hr, Fish) |

General Information

No information available.

12.2. Persistence and degradability

General Information

Persistence No information available.

degradability No information available.

12.3. Bioaccumulative potential

Product Information No information available.

logPow No information available

12.4. Mobility in soil

Soil Given its physical and chemical characteristics, the product generally shows low soil mobility.

Air Loss by evaporation is limited.

Water Insoluble. The product spreads on the surface of the water.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

12.6. Other adverse effects

General Information No information available

13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues / Unused Products Should not be released into the environment. Do not empty into drains. Dispose of in accordance with all applicable national environmental laws and regulations. Where possible recycling is preferred to disposal or incineration.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Other information Refer to section 8 for safety and protective measures for disposal personnel.

MATERIAL SAFETY DATA SHEET

S-OIL PROCESS OIL 60

Date of the previous version: 2018-02-22

Revision Date: 2023-09-11

Version 3

14. TRANSPORT INFORMATION**ADR/RID** Not regulated**IMDG/IMO** Not regulated**ICAO/IATA** Not regulated**ADN** Not regulated**15. REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****International Inventories**EINECS/ELINCS
TSCA
KECL**Further information****15.2. Chemical Safety Assessment**

Chemical Safety Assessment No information available

16. OTHER INFORMATIONFull text of R-phrases referred to under sections 2 and 3
No information available**Abbreviations, acronyms**

Legend Section 8

| | | | |
|----|--------------------|----|-----------------------|
| + | Sensitizer | * | Skin designation |
| ** | Hazard Designation | C: | Carcinogen |
| M: | Mutagen | R: | Toxic to reproduction |

Revision Date: 2023-09-11
Revision Note: *** Indicates updated section.

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the safety data sheet