



S-OIL SEVEN RED #5 SM

MULTI GRADE OIL FOR GASOLINE ENGINE

Product Description

S-OIL SEVEN RED #5 SM is multi grade engine oil for all gasoline engines. It suitable for recent technology engines (multi valve, turbocharged, with/without catalytic converter) and vehicles requiring performance specification API SM.

Applications

- All gasoline engines, especially for most recent technology engines (multi valve, turbocharged, with/without catalytic converter) supercharged or not, in cars
- Suitable for all journeys (in town, on highways) and particularly in severe conditions
- For all driving styles, vigorous speeds in all seasons

Features and Potential Benefits

- Meets API SM requirements, guarantee of an high and constant quality for lubricants
- Ensures easy cold start due to its extreme fluidity at low temperature and maintains a very resistant oil film even at extremely high operating temperature
- Protects mechanical parts and fully preserves the engine power, thus contributing to its youth and strength

Performance Level

- API : SM/CF

Typical Properties

Test Items		Method	Unit	10W-40
Specific Gravity		ASTM D1298	-	0.866
Viscosity	40°C	ASTM D445	cSt	103.8
	100°C	ASTM D445	cSt	15.3
Viscosity Index		ASTM D2270	-	155
Flash Point		ASTM D92	°C	224
Pour Point		ASTM D97	°C	-39

S-OIL CORPORATION
192, Baekbeom-ro, Mapo-gu,
Seoul, 04196, Korea

S-OIL SEVEN RED #5 SM
2019.08.14



This lubricant used recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet is obtainable via your commercial adviser.