



S-OIL SEVEN RED #7 SN

SYNTHETIC GASOLINE ENGINE OIL

Product Description

S-OIL SEVEN RED #7 SN is made by synthetic base oil for all gasoline engines. It suitable for recent technology engines (multi valve, turbocharged, with/without catalytic converter) and vehicles requiring performance specification API SN.

Applications

- All gasoline engines, especially for most recent technology engines (multi valve, turbocharged, with/without catalytic converter) supercharged or not, in cars
- Suitable for all journeys (in town, on highways) and particular in severe conditions
- For all driving styles, vigorous speeds in all seasons
- Suitable to use in LPG/CNG/LNG engine (10W-30, 10W-40, 15W-40, 20W-50)

Features and Potential Benefits

- Meets API SN and ILSAC GF-5 requirements, the guarantee of high and constant quality for lubricants
- Ensures easy cold start due to its extreme fluidity at low temperature and maintains a very resistant oil film even at extremely high operating temperature
- Protects mechanical parts and fully preserves the engine power, thus contributing to its youth and strength
- Low viscosity grades provide reduced friction and create fuel savings which decrease CO2 emissions

Performance Level

- API : SN/CF
- API : SN-RC (5W-20/30, 10W-30)
- ILSAC : GF-5 (5W-20/30, 10W-30)

Typical Properties

	Method	Unit	5W-20	5W-30	5W-40	10W-30	10W-40	15W-40	20W-50
SG	ASTM D1298	-	0.860	0.857	0.847	0.866	0.864	0.871	0.874
Viscosity	40°C	ASTM D445	cSt	51.4	62.7	83.4	69.2	96.9	155.1
	100°C	ASTM D445	cSt	8.6	10.4	13.7	10.2	14.0	17.9
VI	ASTM D2270	-	146	154	168	132	147	133	128
Flash Point	ASTM D92	°C	224	226	238	226	226	234	254
Pour Point	ASTM D97	°C	-42	-43	-38	-41	-39	-34	-27

S-OIL CORPORATION
192, Baekbeom-ro, Mapo-gu,
Seoul, 04196, Korea

S-OIL SEVEN RED #7 SN
2026.04.01.

This lubricant used recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.