



# S-OIL SEVEN RED #7 SL

MULTI GRADE **SYNTHETIC** OIL FOR GASOLINE ENGINE

## Product Description

S-OIL SEVEN RED #7 SL is made by synthetic technology for all gasoline engines. It suitable for recent technology engines (multi valve, turbocharged, with/without catalytic converter) and vehicles requiring performance specification API SL.

## Applications

- All gasoline engines, especially for most recent technology engines (multi valve, turbocharged, with/without catalytic converter) supercharged or not, in cars
- Suitable for all journeys (in town, on highways) and particularly in severe conditions
- For all driving styles, vigorous speeds in all seasons

## Features and Potential Benefits

- Meets API SL and ILSAC GF-3 requirements, guarantee of an high and constant quality for lubricants
- Ensures easy cold start due to its extreme fluidity at low temperature and maintains a very resistant oil film even at extremely high operating temperature
- Protects mechanical parts and fully preserves the engine power, thus contributing to its youth and strength

## Performance Level

- API : SL/CF
- ILSAC : GF-3

## Typical Properties

Test Items	Method	Unit	5W-30	
Specific Gravity	ASTM D1298	-	0.858	
Viscosity	40°C	ASTM D445	cSt	61.9
	100°C	ASTM D445	cSt	10.2
Viscosity Index	ASTM D2270	-	151	
Flash Point	ASTM D92	°C	234	
Pour Point	ASTM D97	°C	-39	

S-OIL CORPORATION  
192, Baekbeom-ro, Mapo-gu,  
Seoul, 04196, Korea

S-OIL SEVEN RED #7 SL  
2025.07.01



This lubricant used recommended and for the application for which it has been designed does not present any particular risk.  
A material safety data sheet is obtainable via your commercial adviser.