



S-OIL GREASE LT 2

Description

S-OIL GREASE LT 2 grease is designed for plastic and metal lubrication based highly refined mineral oil thickened with special lithium soap and various additives.

Suitable for long-term lubrication equipment requiring corrosion protection and oxidation stability Grease is suitable for plastic and steel lubrication requiring excellent wear resistance and low noise. Also it prevents grease and oil spread to other components.

Advantages

- Excellent compatibility between plastic and steel lubrication
- Good rust resistance and oxidation stability
- Anti-wear and anti-load properties
- Service temperature: -40°C ~ +150°C

Main Components

- Lithium soap thickener
- Refined mineral oil
- Special solid lubricants

Applications

- Lubrication for plastic to plastic
- Lubrication for metal to metal
- Lubrication for metal to plastic
- Parts requiring non-spread oils

Typical Properties

Test Items		Method	Unit	Properties
Appearance		-	-	Light Yellow
Worked Penetration	25°C	ASTM D 217	0.1mm	280
Dropping Point		ASTM D 566	°C	201
Copper strip corrosion		ASTM D 4048	-	1a

S-OIL CORPORATION
192, Baekbeom-ro, Mapo-gu,
Seoul, 04196, Korea

S-OIL GREASE LT 2
2025.03.05

This lubricant used recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet is obtainable via your commercial adviser.