



S-OIL SEVEN RED #5 SJ

MULTI GRADE OIL FOR GASOLINE ENGINES

Product Description

S-OIL SEVEN RED #5 SJ is multi grade engine oil for all gasoline engines. It suitable for recent technology engines (multi valve, turbocharged, with/without catalytic converter) and vehicles requiring performance specification API SJ.

Applications

- All gasoline engines, especially for most recent technology engines (multi valve, turbocharged, with/without catalytic converter) supercharged or not, in cars
- Suitable for all journeys (in town, on highways) and particularly in severe conditions
- For all driving styles, vigorous speeds in all seasons

Features and Potential Benefits

- Meets API SJ and ILSAC GF-2 (5W-30 and 10W-30) requirements, guarantee of an high and constant quality for lubricants
- Ensures easy cold start due to its extreme fluidity at low temperature and maintains a very resistant oil film even at extremely high operating temperature
- Gives the engine an excellent wear protection, develops performance and power
- Keeps the engine's most sensitive parts clean thanks to its advanced detergent and dispersive additives

Performance Level

- API : SJ
- ILSAC : GF-2 (5W-30, 10W-30)

Typical Properties

Test Items	Method	Unit	5W-30	10W-30	10W-40
SG	ASTM D1298	-	0.8584	0.8681	0.869
Viscosity	40°C	ASTM D445	61.9	72.6	94.73
	100°C	ASTM D445	10.2	10.9	13.8
VI	ASTM D2270	-	151	139	147
Flash Point	ASTM D92	°C	234	228	222
Pour Point	ASTM D97	°C	-39	-34	-33

S-OIL CORPORATION
192, Baekbeom-ro, Mapo-gu,
Seoul, 04196, Korea

S-OIL SEVEN RED #5 SJ
2025.07.01



This lubricant used recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet is obtainable via your commercial adviser.